

STC-SS SERIES

The STC-SS Series suppressors are designed for the water and wastewater industry. These multi-stage hybrid suppressors address overvoltage transients with gas tube and silicon avalanche technology. In addition, sneak and electrical fault currents are mitigated with PTC devices which consist of solid-state resettable fuses. The units are encapsulated in stainless steel pipe nipples making them suitable for use in severe environments.

APPLICATIONS

- Water and wastewater
- Industrial applications •

FEATURES

- Automatic recovery features make it ideal for use in severe environments
- Transient protection for low-voltage signal lines
- Gas tube and silicon avalanche technology •
- Sneak/fault current protection •
- Resettable solid-state fuses PTCs .
- Differential and common mode protection •
- Multi-stage hyrbid suppressor •

SELECTION TABLE

Catalog Number	Description
STCSS640362	1/2" Metal Conduit Capped

- Encapsulated in stainless steel pipe nipples
- UL497B Certified
- Five year limited warranty

CERTIFICATIONS AND COMPLIANCES

- (UL) Listed
- UL 497B
- RoHS Compliant



CONSIDER IT SOLVED[®]




For product information:

SPECIFICATIONS

Description	Signal Line Protection
Operating Voltage	28 Vdc
Maximum Operating Current	150 mA
Clamping Voltage	(L-G) 36 Vdc (L-L) 72 Vdc
Peak Surge Current	10 kA (8x20 μs)
SPD Technology	GDT/PTC/SAD Hybrid
Frequency Range	0 to 20 MHz
Insertion Loss	<0.1 dB at 20 MHz
Series Resistance (per Conductor)	5 Ohms (typical)
Capacitance (Zero Volts Bias)	(L-G) 1200 pf (typical) (L-L) 600 pf (typical)
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Life Cycle	400 @ 500 Amps (10x1000 μs)
Weight - lbs (kg)	0.35 (0.16)
Certifications	UL 497B
Limited warranty	5 year limited warranty

DIMENSIONAL DRAWING



 United States:
 1.800.377.4384 | Asia/Pacific:
 + 65.6891.7600 | Australia:
 + 61.3.9721.0387

 Brazil:
 São Paulo/SP + 55.11.2122.5777 | Brazil:
 Camaçari/BA + 55.71.3496.4427 | Canada:
 + 1.888.765.2226

 China:
 + 86.21.3418.3888 | Europe:
 + 33.3.2254.1390 | Mexico/Latin America:
 + 52.55.5809.5049

 Middle
 East/Africa/India:
 + 971.4.811.8100
 www.solahd.com



